

Siemens  
EcoTech



SIMATIC S7-1200, CPU 1214C, compact CPU, DC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, power supply: DC 20.4-28.8 V DC, program/data memory 150 KB



Figure similar

| General information                   |                                          |
|---------------------------------------|------------------------------------------|
| Product type designation              | CPU 1214C DC/DC/relay                    |
| Firmware version                      | V4.7                                     |
| Engineering with                      |                                          |
| • Programming package                 | STEP 7 V20 or higher                     |
| Supply voltage                        |                                          |
| Rated value (DC)                      |                                          |
| • 24 V DC                             | Yes                                      |
| permissible range, lower limit (DC)   | 20.4 V                                   |
| permissible range, upper limit (DC)   | 28.8 V                                   |
| Reverse polarity protection           | Yes                                      |
| Load voltage L+                       |                                          |
| • Rated value (DC)                    | 24 V                                     |
| • permissible range, lower limit (DC) | 20.4 V                                   |
| • permissible range, upper limit (DC) | 28.8 V                                   |
| Input current                         |                                          |
| Current consumption (rated value)     | 500 mA; CPU only                         |
| Current consumption, max.             | 1 500 mA; CPU with all expansion modules |
| Inrush current, max.                  | 12 A; at 28.8 V                          |
| I²t                                   | 0.8 A²·s                                 |
| Output current                        |                                          |
| for backplane bus (5 V DC), max.      | 1 600 mA; Max. 5 V DC for SM and CM      |
| Encoder supply                        |                                          |
| 24 V encoder supply                   |                                          |
| • 24 V                                | L+ minus 4 V DC min.                     |
| Power loss                            |                                          |
| Power loss, typ.                      | 12 W                                     |
| Storage                               |                                          |
| Work memory                           |                                          |
| • Integrated                          | 150 kbyte                                |
| Load memory                           |                                          |
| • Integrated                          | 4 Mbyte                                  |
| • Plug-in (SIMATIC Memory Card), max. | with SIMATIC memory card                 |
| Backup                                |                                          |
| • present                             | Yes                                      |

|                                                           |                                                                                                                                                                     |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • maintenance-free                                        | Yes                                                                                                                                                                 |
| • Without battery                                         | Yes                                                                                                                                                                 |
| <b>CPU processing times</b>                               |                                                                                                                                                                     |
| for bit operations, typ.                                  | 0.08 µs; / instruction                                                                                                                                              |
| for word operations, typ.                                 | 1.7 µs; / instruction                                                                                                                                               |
| for floating point arithmetic, typ.                       | 2.3 µs; / instruction                                                                                                                                               |
| <b>CPU-blocks</b>                                         |                                                                                                                                                                     |
| Number of blocks (total)                                  | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| <b>OB</b>                                                 |                                                                                                                                                                     |
| • Number, max.                                            | Limited only by RAM for code                                                                                                                                        |
| <b>Data areas and their retentivity</b>                   |                                                                                                                                                                     |
| Retentive data area (incl. timers, counters, flags), max. | 14 kbyte                                                                                                                                                            |
| <b>Flag</b>                                               |                                                                                                                                                                     |
| • Size, max.                                              | 8 kbyte; Size of bit memory address area                                                                                                                            |
| <b>Local data</b>                                         |                                                                                                                                                                     |
| • per priority class, max.                                | 16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB                                                                                     |
| <b>Address area</b>                                       |                                                                                                                                                                     |
| <b>Process image</b>                                      |                                                                                                                                                                     |
| • Inputs, adjustable                                      | 1 kbyte                                                                                                                                                             |
| • Outputs, adjustable                                     | 1 kbyte                                                                                                                                                             |
| <b>Hardware configuration</b>                             |                                                                                                                                                                     |
| Number of modules per system, max.                        | 3 comm. modules, 1 signal board, 8 signal modules                                                                                                                   |
| • number of expansion boards (SB, CB, BB)                 | 1                                                                                                                                                                   |
| • number of signal modules (SM)                           | 8                                                                                                                                                                   |
| • number of communications modules (CM)                   | 3                                                                                                                                                                   |
| <b>Time of day</b>                                        |                                                                                                                                                                     |
| <b>Clock</b>                                              |                                                                                                                                                                     |
| • Hardware clock (real-time)                              | Yes                                                                                                                                                                 |
| • Backup time                                             | 480 h; Typical                                                                                                                                                      |
| • Deviation per day, max.                                 | ±60 s/month at 25 °C                                                                                                                                                |
| <b>Digital inputs</b>                                     |                                                                                                                                                                     |
| Number of digital inputs                                  | 14; Integrated                                                                                                                                                      |
| • of which inputs usable for technological functions      | 6; HSC (High Speed Counting)                                                                                                                                        |
| Sourcing/sinking input                                    | Yes                                                                                                                                                                 |
| <b>Number of simultaneously controllable inputs</b>       |                                                                                                                                                                     |
| <b>all mounting positions</b>                             |                                                                                                                                                                     |
| — up to 40 °C, max.                                       | 14                                                                                                                                                                  |
| <b>Input voltage</b>                                      |                                                                                                                                                                     |
| • Rated value (DC)                                        | 24 V                                                                                                                                                                |
| • for signal "0"                                          | 5 V DC at 1 mA                                                                                                                                                      |
| • for signal "1"                                          | 15 V DC at 2.5 mA                                                                                                                                                   |
| <b>Input delay (for rated value of input voltage)</b>     |                                                                                                                                                                     |
| <b>for standard inputs</b>                                |                                                                                                                                                                     |
| — Parameterizable                                         | 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 µs; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms                             |
| — at "0" to "1", min.                                     | 0.2 ms                                                                                                                                                              |
| — at "0" to "1", max.                                     | 12.8 ms                                                                                                                                                             |
| <b>for interrupt inputs</b>                               |                                                                                                                                                                     |
| — parameterizable                                         | Yes                                                                                                                                                                 |
| <b>for technological functions</b>                        |                                                                                                                                                                     |
| — Parameterizable                                         | Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz                                                                                       |
| <b>Cable length</b>                                       |                                                                                                                                                                     |
| • shielded, max.                                          | 500 m; 50 m for technological functions                                                                                                                             |
| • unshielded, max.                                        | 300 m; for technological functions: No                                                                                                                              |
| <b>Digital outputs</b>                                    |                                                                                                                                                                     |
| Number of digital outputs                                 | 10; Relays                                                                                                                                                          |
| <b>Switching capacity of the outputs</b>                  |                                                                                                                                                                     |

|                                                        |                                                        |
|--------------------------------------------------------|--------------------------------------------------------|
| • with resistive load, max.                            | 2 A                                                    |
| • on lamp load, max.                                   | 30 W with DC, 200 W with AC                            |
| Output delay with resistive load                       |                                                        |
| • "0" to "1", max.                                     | 10 ms; max.                                            |
| • "1" to "0", max.                                     | 10 ms; max.                                            |
| Relay outputs                                          |                                                        |
| • Number of relay outputs                              | 10                                                     |
| • Number of operating cycles, max.                     | mechanically 10 million, at rated load voltage 100 000 |
| Cable length                                           |                                                        |
| • shielded, max.                                       | 500 m                                                  |
| • unshielded, max.                                     | 150 m                                                  |
| Analog inputs                                          |                                                        |
| Number of analog inputs                                | 2                                                      |
| Input ranges                                           |                                                        |
| • Voltage                                              | Yes                                                    |
| Input ranges (rated values), voltages                  |                                                        |
| • 0 to +10 V                                           | Yes                                                    |
| — Input resistance (0 to 10 V)                         | ≥100k ohms                                             |
| Cable length                                           |                                                        |
| • shielded, max.                                       | 100 m; twisted and shielded                            |
| Analog outputs                                         |                                                        |
| Number of analog outputs                               | 0                                                      |
| Analog value generation for the inputs                 |                                                        |
| Integration and conversion time/resolution per channel |                                                        |
| • Resolution with overrange (bit including sign), max. | 10 bit                                                 |
| • Integration time, parameterizable                    | Yes                                                    |
| • Conversion time (per channel)                        | 625 µs                                                 |
| Encoder                                                |                                                        |
| Connectable encoders                                   |                                                        |
| • 2-wire sensor                                        | Yes                                                    |
| Interfaces                                             |                                                        |
| Number of PROFINET interfaces                          | 1                                                      |
| 1. Interface                                           |                                                        |
| Interface type                                         | PROFINET                                               |
| Isolated                                               | Yes                                                    |
| automatic detection of transmission rate               | Yes                                                    |
| Autonegotiation                                        | Yes                                                    |
| Autocrossing                                           | Yes                                                    |
| Interface types                                        |                                                        |
| • RJ 45 (Ethernet)                                     | Yes                                                    |
| • Number of ports                                      | 1                                                      |
| • integrated switch                                    | No                                                     |
| Protocols                                              |                                                        |
| • PROFINET IO Controller                               | Yes                                                    |
| • PROFINET IO Device                                   | Yes                                                    |
| • SIMATIC communication                                | Yes                                                    |
| • Open IE communication                                | Yes; Optionally also encrypted                         |
| • Web server                                           | Yes                                                    |
| • Media redundancy                                     | No                                                     |
| PROFINET IO Controller                                 |                                                        |
| • Transmission rate, max.                              | 100 Mbit/s                                             |
| Services                                               |                                                        |
| — PG/OP communication                                  | Yes; encryption with TLS V1.3 pre-selected             |
| — Isochronous mode                                     | No                                                     |
| — IRT                                                  | No                                                     |
| — PROFIenergy                                          | No                                                     |
| — Prioritized startup                                  | Yes                                                    |
| — Number of IO devices with prioritized startup, max.  | 16                                                     |
| — Number of connectable IO Devices, max.               | 16                                                     |

|                                                                               |                                                                                                                                                                             |
|-------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| — Number of connectable IO Devices for RT, max.                               | 16                                                                                                                                                                          |
| — of which in line, max.                                                      | 16                                                                                                                                                                          |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8                                                                                                                                                                           |
| — Updating time                                                               | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |
| <b>PROFINET IO Device</b>                                                     |                                                                                                                                                                             |
| <b>Services</b>                                                               |                                                                                                                                                                             |
| — PG/OP communication                                                         | Yes; encryption with TLS V1.3 pre-selected                                                                                                                                  |
| — Isochronous mode                                                            | No                                                                                                                                                                          |
| — IRT                                                                         | No                                                                                                                                                                          |
| — Dynamic Frame Packing (DFP)                                                 | No                                                                                                                                                                          |
| — PROFINergy                                                                  | Yes                                                                                                                                                                         |
| — Prioritized startup                                                         | Yes                                                                                                                                                                         |
| — Shared device                                                               | Yes                                                                                                                                                                         |
| — Number of IO Controllers with shared device, max.                           | 2                                                                                                                                                                           |
| — Asset management record                                                     | Yes                                                                                                                                                                         |
| <b>Protocols</b>                                                              |                                                                                                                                                                             |
| Supports protocol for PROFINET IO                                             | Yes                                                                                                                                                                         |
| PROFIsafe                                                                     | No                                                                                                                                                                          |
| PROFIBUS                                                                      | Yes; CM 1243-5 (master) or CM 1242-5 (slave) required                                                                                                                       |
| OPC UA                                                                        | Yes; OPC UA Server                                                                                                                                                          |
| AS-Interface                                                                  | Yes; CM 1243-2 required                                                                                                                                                     |
| <b>Protocols (Ethernet)</b>                                                   |                                                                                                                                                                             |
| • TCP/IP                                                                      | Yes                                                                                                                                                                         |
| • DHCP                                                                        | No                                                                                                                                                                          |
| • SNMP                                                                        | Yes                                                                                                                                                                         |
| • DCP                                                                         | Yes                                                                                                                                                                         |
| • LLDP                                                                        | Yes                                                                                                                                                                         |
| <b>Redundancy mode</b>                                                        |                                                                                                                                                                             |
| • PROFINET system redundancy (S2)                                             | No                                                                                                                                                                          |
| • PROFINET system redundancy (R1)                                             | No                                                                                                                                                                          |
| <b>Media redundancy</b>                                                       |                                                                                                                                                                             |
| — MRP                                                                         | No                                                                                                                                                                          |
| — MRP interconnection, supported                                              | No                                                                                                                                                                          |
| — MRPD                                                                        | No                                                                                                                                                                          |
| <b>SIMATIC communication</b>                                                  |                                                                                                                                                                             |
| • S7 routing                                                                  | Yes                                                                                                                                                                         |
| <b>Open IE communication</b>                                                  |                                                                                                                                                                             |
| • TCP/IP                                                                      | Yes                                                                                                                                                                         |
| — Data length, max.                                                           | 8 kbyte                                                                                                                                                                     |
| • ISO-on-TCP (RFC1006)                                                        | Yes                                                                                                                                                                         |
| — Data length, max.                                                           | 8 kbyte                                                                                                                                                                     |
| • UDP                                                                         | Yes                                                                                                                                                                         |
| — Data length, max.                                                           | 1 472 byte                                                                                                                                                                  |
| <b>Web server</b>                                                             |                                                                                                                                                                             |
| • supported                                                                   | Yes                                                                                                                                                                         |
| • User-defined websites                                                       | Yes                                                                                                                                                                         |
| <b>OPC UA</b>                                                                 |                                                                                                                                                                             |
| • Runtime license required                                                    | Yes; "Basic" license required                                                                                                                                               |
| • OPC UA Server                                                               | Yes; data access (read, write, subscribe), method call, runtime license required                                                                                            |
| — Application authentication                                                  | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256                                                                                             |
| — User authentication                                                         | "anonymous" or by user name & password                                                                                                                                      |
| — Number of sessions, max.                                                    | 10                                                                                                                                                                          |
| — Number of subscriptions per session, max.                                   | 5                                                                                                                                                                           |
| — Sampling interval, min.                                                     | 100 ms                                                                                                                                                                      |
| — Publishing interval, min.                                                   | 200 ms                                                                                                                                                                      |
| — Number of server methods, max.                                              | 20                                                                                                                                                                          |

|                                                                                       |                                                                                                                                                                                                                                                                                    |
|---------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| — Number of monitored items, recommended max.                                         | 1 000                                                                                                                                                                                                                                                                              |
| — Number of server interfaces, max.                                                   | 2                                                                                                                                                                                                                                                                                  |
| — Number of nodes for user-defined server interfaces, max.                            | 2 000                                                                                                                                                                                                                                                                              |
| <b>Further protocols</b>                                                              |                                                                                                                                                                                                                                                                                    |
| • MODBUS                                                                              | Yes                                                                                                                                                                                                                                                                                |
| <b>Communication functions</b>                                                        |                                                                                                                                                                                                                                                                                    |
| <b>S7 communication</b>                                                               |                                                                                                                                                                                                                                                                                    |
| • supported                                                                           | Yes                                                                                                                                                                                                                                                                                |
| • as server                                                                           | Yes                                                                                                                                                                                                                                                                                |
| • As client                                                                           | Yes                                                                                                                                                                                                                                                                                |
| • User data per job, max.                                                             | See online help (S7 communication, user data size)                                                                                                                                                                                                                                 |
| <b>Number of connections</b>                                                          |                                                                                                                                                                                                                                                                                    |
| • overall                                                                             | PG Connections: 4 reserved / 4 max; HMI Connections: 12 reserved / 18 max; S7 Connections: 8 reserved / 14 max; Open User Connections: 8 reserved / 14 max; Web Connections: 2 reserved / 30 max; OPC UA Connections: 0 reserved / 10 max; Total Connections: 34 reserved / 68 max |
| <b>Test commissioning functions</b>                                                   |                                                                                                                                                                                                                                                                                    |
| <b>Status/control</b>                                                                 |                                                                                                                                                                                                                                                                                    |
| • Status/control variable                                                             | Yes                                                                                                                                                                                                                                                                                |
| • Variables                                                                           | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters                                                                                                                                                                                                               |
| <b>Forcing</b>                                                                        |                                                                                                                                                                                                                                                                                    |
| • Forcing                                                                             | Yes                                                                                                                                                                                                                                                                                |
| <b>Diagnostic buffer</b>                                                              |                                                                                                                                                                                                                                                                                    |
| • present                                                                             | Yes                                                                                                                                                                                                                                                                                |
| <b>Traces</b>                                                                         |                                                                                                                                                                                                                                                                                    |
| • Number of configurable Traces                                                       | 2                                                                                                                                                                                                                                                                                  |
| • Memory size per trace, max.                                                         | 512 kbyte                                                                                                                                                                                                                                                                          |
| <b>Interrupts/diagnostics/status information</b>                                      |                                                                                                                                                                                                                                                                                    |
| <b>Diagnostics indication LED</b>                                                     |                                                                                                                                                                                                                                                                                    |
| • RUN/STOP LED                                                                        | Yes                                                                                                                                                                                                                                                                                |
| • ERROR LED                                                                           | Yes                                                                                                                                                                                                                                                                                |
| • MAINT LED                                                                           | Yes                                                                                                                                                                                                                                                                                |
| <b>Integrated Functions</b>                                                           |                                                                                                                                                                                                                                                                                    |
| <b>Counter</b>                                                                        |                                                                                                                                                                                                                                                                                    |
| • Number of counters                                                                  | 6                                                                                                                                                                                                                                                                                  |
| • Counting frequency, max.                                                            | 100 kHz                                                                                                                                                                                                                                                                            |
| Frequency measurement                                                                 | Yes                                                                                                                                                                                                                                                                                |
| controlled positioning                                                                | Yes                                                                                                                                                                                                                                                                                |
| Number of position-controlled positioning axes, max.                                  | 8                                                                                                                                                                                                                                                                                  |
| Number of positioning axes via pulse-direction interface                              | Up to 4 with SB 1222                                                                                                                                                                                                                                                               |
| PID controller                                                                        | Yes                                                                                                                                                                                                                                                                                |
| Number of alarm inputs                                                                | 4                                                                                                                                                                                                                                                                                  |
| <b>Potential separation</b>                                                           |                                                                                                                                                                                                                                                                                    |
| <b>Potential separation digital inputs</b>                                            |                                                                                                                                                                                                                                                                                    |
| • Potential separation digital inputs                                                 | 500 V AC for 1 minute                                                                                                                                                                                                                                                              |
| • between the channels, in groups of                                                  | 1                                                                                                                                                                                                                                                                                  |
| <b>Potential separation digital outputs</b>                                           |                                                                                                                                                                                                                                                                                    |
| • Potential separation digital outputs                                                | Relays                                                                                                                                                                                                                                                                             |
| • between the channels                                                                | No                                                                                                                                                                                                                                                                                 |
| • between the channels, in groups of                                                  | 2                                                                                                                                                                                                                                                                                  |
| <b>EMC</b>                                                                            |                                                                                                                                                                                                                                                                                    |
| <b>Interference immunity against discharge of static electricity</b>                  |                                                                                                                                                                                                                                                                                    |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes                                                                                                                                                                                                                                                                                |
| — Test voltage at air discharge                                                       | 8 kV                                                                                                                                                                                                                                                                               |
| — Test voltage at contact discharge                                                   | 6 kV                                                                                                                                                                                                                                                                               |
| <b>Interference immunity to cable-borne interference</b>                              |                                                                                                                                                                                                                                                                                    |
| • Interference immunity on supply lines acc. to IEC 61000-4-4                         | Yes                                                                                                                                                                                                                                                                                |

|                                                                                               |                                                                                                                                                                               |
|-----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • Interference immunity on signal cables acc. to IEC 61000-4-4                                | Yes                                                                                                                                                                           |
| Interference immunity against voltage surge                                                   |                                                                                                                                                                               |
| • Interference immunity on supply lines acc. to IEC 61000-4-5                                 | Yes                                                                                                                                                                           |
| Interference immunity against conducted variable disturbance induced by high-frequency fields |                                                                                                                                                                               |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6                | Yes                                                                                                                                                                           |
| Emission of radio interference acc. to EN 55 011                                              |                                                                                                                                                                               |
| • Limit class A, for use in industrial areas                                                  | Yes; Group 1                                                                                                                                                                  |
| • Limit class B, for use in residential areas                                                 | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011                                                                |
| Degree and class of protection                                                                |                                                                                                                                                                               |
| IP degree of protection                                                                       | IP20                                                                                                                                                                          |
| Standards, approvals, certificates                                                            |                                                                                                                                                                               |
| Siemens Eco Profile (SEP)                                                                     | Siemens EcoTech                                                                                                                                                               |
| CE mark                                                                                       | Yes                                                                                                                                                                           |
| UL approval                                                                                   | Yes                                                                                                                                                                           |
| cULus                                                                                         | Yes                                                                                                                                                                           |
| FM approval                                                                                   | Yes                                                                                                                                                                           |
| RCM (formerly C-TICK)                                                                         | Yes                                                                                                                                                                           |
| KC approval                                                                                   | Yes                                                                                                                                                                           |
| Marine approval                                                                               | Yes                                                                                                                                                                           |
| Ecological footprint                                                                          |                                                                                                                                                                               |
| • environmental product declaration                                                           | Yes; type II acc. to ISO 14021                                                                                                                                                |
| Global warming potential                                                                      |                                                                                                                                                                               |
| — global warming potential, (total) [CO2 eq]                                                  | 111 kg                                                                                                                                                                        |
| — global warming potential, (during production) [CO2 eq]                                      | 20.1 kg                                                                                                                                                                       |
| — global warming potential, (during operation) [CO2 eq]                                       | 91.5 kg                                                                                                                                                                       |
| — global warming potential, (after end of life cycle) [CO2 eq]                                | -0.9 kg                                                                                                                                                                       |
| Ambient conditions                                                                            |                                                                                                                                                                               |
| Free fall                                                                                     |                                                                                                                                                                               |
| • Fall height, max.                                                                           | 0.3 m; five times, in product package                                                                                                                                         |
| Ambient temperature during operation                                                          |                                                                                                                                                                               |
| • min.                                                                                        | -20 °C                                                                                                                                                                        |
| • max.                                                                                        | 60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical |
| • horizontal installation, min.                                                               | -20 °C                                                                                                                                                                        |
| • horizontal installation, max.                                                               | 60 °C                                                                                                                                                                         |
| • vertical installation, min.                                                                 | -20 °C                                                                                                                                                                        |
| • vertical installation, max.                                                                 | 50 °C                                                                                                                                                                         |
| Ambient temperature during storage/transportation                                             |                                                                                                                                                                               |
| • min.                                                                                        | -40 °C                                                                                                                                                                        |
| • max.                                                                                        | 70 °C                                                                                                                                                                         |
| Air pressure acc. to IEC 60068-2-13                                                           |                                                                                                                                                                               |
| • Operation, min.                                                                             | 795 hPa                                                                                                                                                                       |
| • Operation, max.                                                                             | 1 080 hPa                                                                                                                                                                     |
| • Storage/transport, min.                                                                     | 660 hPa                                                                                                                                                                       |
| • Storage/transport, max.                                                                     | 1 080 hPa                                                                                                                                                                     |
| Altitude during operation relating to sea level                                               |                                                                                                                                                                               |
| • Installation altitude, min.                                                                 | -1 000 m                                                                                                                                                                      |
| • Installation altitude, max.                                                                 | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual                                                                                                        |
| Relative humidity                                                                             |                                                                                                                                                                               |
| • Operation, max.                                                                             | 95 %; no condensation                                                                                                                                                         |
| Vibrations                                                                                    |                                                                                                                                                                               |
| • Vibration resistance during operation acc. to IEC 60068-2-6                                 | 2 g (m/s²) wall mounting, 1 g (m/s²) DIN rail                                                                                                                                 |
| • Operation, tested according to IEC 60068-2-6                                                | Yes                                                                                                                                                                           |

|                                                 |                                                                                           |         |                |
|-------------------------------------------------|-------------------------------------------------------------------------------------------|---------|----------------|
| Shock testing                                   |                                                                                           |         |                |
| • tested according to IEC 60068-2-27            | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |         |                |
| Pollutant concentrations                        |                                                                                           |         |                |
| • SO2 at RH < 60% without condensation          | S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free                               |         |                |
| Configuration                                   |                                                                                           |         |                |
| Programming                                     |                                                                                           |         |                |
| Programming language                            |                                                                                           |         |                |
| — LAD                                           | Yes                                                                                       |         |                |
| — FBD                                           | Yes                                                                                       |         |                |
| — SCL                                           | Yes                                                                                       |         |                |
| Know-how protection                             |                                                                                           |         |                |
| • User program protection/password protection   | Yes                                                                                       |         |                |
| • Copy protection                               | Yes                                                                                       |         |                |
| • Block protection                              | Yes                                                                                       |         |                |
| Access protection                               |                                                                                           |         |                |
| • protection of confidential configuration data | Yes                                                                                       |         |                |
| • Protection level: Write protection            | Yes                                                                                       |         |                |
| • Protection level: Read/write protection       | Yes                                                                                       |         |                |
| • Protection level: Complete protection         | Yes                                                                                       |         |                |
| • User administration                           | Yes; device-wide                                                                          |         |                |
| • Number of users                               | 42                                                                                        |         |                |
| • Number of groups                              | 14                                                                                        |         |                |
| • Number of roles                               | 20                                                                                        |         |                |
| Cycle time monitoring                           |                                                                                           |         |                |
| • can be set                                    | Yes                                                                                       |         |                |
| Dimensions                                      |                                                                                           |         |                |
| Width                                           | 110 mm                                                                                    |         |                |
| Height                                          | 100 mm                                                                                    |         |                |
| Depth                                           | 75 mm                                                                                     |         |                |
| Weights                                         |                                                                                           |         |                |
| Weight, approx.                                 | 435 g                                                                                     |         |                |
| Classifications                                 |                                                                                           |         |                |
|                                                 |                                                                                           | Version | Classification |
|                                                 | eClass                                                                                    | 16      | 27-24-22-07    |
|                                                 | eClass                                                                                    | 14      | 27-24-22-07    |
|                                                 | eClass                                                                                    | 12      | 27-24-22-07    |
|                                                 | eClass                                                                                    | 9.1     | 27-24-22-07    |
|                                                 | eClass                                                                                    | 9       | 27-24-22-07    |
|                                                 | eClass                                                                                    | 8       | 27-24-22-07    |
|                                                 | eClass                                                                                    | 7.1     | 27-24-22-07    |
|                                                 | eClass                                                                                    | 6       | 27-24-22-07    |
|                                                 | ETIM                                                                                      | 10      | EC000236       |
|                                                 | ETIM                                                                                      | 9       | EC000236       |
|                                                 | ETIM                                                                                      | 8       | EC000236       |
|                                                 | ETIM                                                                                      | 7       | EC000236       |
|                                                 | IDEA                                                                                      | 4       | 3565           |
|                                                 | UNSPSC                                                                                    | 15      | 32-15-17-05    |

|                          |  |  |  |
|--------------------------|--|--|--|
| Approvals / Certificates |  |  |  |
| General Product Approval |  |  |  |

[Miscellaneous](#)

[Manufacturer Declaration](#)



[Metrological Approval](#)

## General Product Approval



[Miscellaneous](#)



[China RoHS](#)

[Manufacturer Declaration](#)

EMV

For use in hazardous locations

Maritime application



[EM](#)



Maritime application

Environment

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)



Environment

Industrial Communication

Siemens  
EcoTech



[PROFINET](#)

last modified:

5/21/2026