

*** spare part *** SIMATIC S7-200, PC/PPI cable MM multimaster, for connection of S7-200 to serial PC interface, supports Freeport and GSM modems

General information	
Product type designation	PC/PPI multi-master
Supply voltage	
Design of the power supply	from CPU
Interfaces	
Point-to-point connection	
• Transmission rate, max.	187.5 kbit/s; 9.6 / 19.3 / 187.5 kbit/s; setting: DIP switch; RS232 not required
Protocols	
PPI	Yes; 10/11 bit
ASCII	Yes; Freeport
Interrupts/diagnostics/status information	
LED status display	Tx (green): RS-232-transmit indication; Rx (green): RS-232-receive indication; PPI (green): RS-485-transmit indication
Potential separation	
Potential separation exists	Yes
Cables	
Cable length	5.63 m
Weights	
Weight, approx.	300 g
Classifications	

	Version	Classification
eClass	16	27-24-22-20
eClass	14	27-24-22-20
eClass	12	27-24-22-20
eClass	9.1	27-24-22-20
eClass	9	27-24-22-20
eClass	8	27-24-92-05
eClass	7.1	27-24-92-05
eClass	6	27-24-92-05
ETIM	10	EC000237
ETIM	9	EC000237
ETIM	8	EC000237
ETIM	7	EC000237
IDEA	4	3553
UNSPSC	15	32-15-17-03

Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



[China RoHS](#)

[Manufacturer Declaration](#)

For use in hazardous locations	Environment
--------------------------------	-------------



[FM](#)



[CCC-Ex](#)

[China RoHS](#)

last modified:

8/24/2025